


# HEATMOR

STAINLESS STEEL OUTDOOR FURNACES



## X-SERIES



*Manufacturing quality outdoor furnaces since 1984.*

The Longest Lasting, Most Energy Efficient  
Stainless Steel Outdoor Furnace in the Industry.

[www.heatmor.com](http://www.heatmor.com)

## X-SERIES FURNACES

Specifications	Model 200 X	Model 350 X
Overall Width (Inches)	50	50
Base Width (Inches) (Footprint)	46.5	46.5
Overall Height (Inches)	82.5	82.5
Overall Length (Inches)	95	95
Base Length (Inches) (Footprint)	83.75	83.75
Total Weight (lbs., without water)	1835	1980
Water Capacity (U.S. gallons)	310	270
Forced Draft (C.F.M.)	150	2 X 150
Chimney Size (Inches)	8	8
Maximum Wood Length (Inches)	19	30
Insulated Heating Area (Sq. Ft.)*		
1 Loading/day	2500	4000
2 Loading/day	5000	8000
Firebox Width (Inches)	23.75	23.75
Firebox Length (Inches)	24	36
Firebox Height (Inches)	27.5	27.5
Volume of Firebox (Cu. Ft.)	14	21
Firebox Door Size (Inches) (W x H)	20 x 18	20 x 18
Flue Transfer Area (Sq. Ft.)	39.75	39.75
BTU's (maximum)**	200,000	280,000
Water Jacket Steel	409 Stainless	409 Stainless
Gauge	10	10
Firebox Steel	409 Stainless	409 Stainless
Gauge	10	10
Base Steel	409 Stainless	409 Stainless
Gauge	14	14
Base of Unit to Bottom of Loading Door (Inches)	24	24
Warranty - Workmanship	Limited Lifetime	Limited Lifetime
Warranty - Corrosion	Limited Lifetime	Limited Lifetime
Approvals Test Standards	UL 2523-2009 CSA-B366.1-11	UL 2523-2009 CSA-B366.1-11
Hook-ups	Back	Back
Type of Fuel	Wood	Wood
Electrical Supply	115 V, 60HZ, 1 Phase	115 V, 60HZ, 1 Phase

\* This is an estimate only. Actual loadings per day may vary depending on structures heated, type of wood used, and climate.

\*\* This value should only be used as an indication of the furnace's heat recovery ability. Sustained outputs at this rate will increase the loadings per day. Some types of wood may prevent the furnace from reaching this maximum output.

### PAD SPECIFICATIONS

Pad thickness must be at least 4" but not to exceed 12".

All measurements in inches.

With the HEATMOR™ system, a concrete pad is required upon installation.

Manufactured By:

# HEATMOR™

105 Industrial Pk. Ct. NE, PO Box 787

Warroad, MN 56763

www.heatmor.com

Models 200x & 350x

